RFID HF Secure Digital RFID Card



Frequenza/Standard Frequency:13,56 MHz. ISO 15693, ISO 14443-A/-B Interfacce &am...

Valutazione: Nessuna valutazione
Fai una domanda su questo prodotto

Produttore: SoftWork

Descrizione

Frequenza/Standard

Frequency:13,56 MHz.

ISO 15693, ISO 14443-A/-B

Interfacce & I/O

SDIO (Secure Digital).

LED Indicator for standby, search and data communications

Antenna

Integrated Antenna

Applicazioni

Designed to plug into any Personal Digital Assistant (PDA), Smartphone or other hand-held device with an SD

slot.

Dati Tecnici

Power supply via SDIO

Low Power Consumption:

- 5 mA standby

- 150 mA field scanning

Compact and reliable design.

Caratteristiche

Microsoft Pocket PC, Win Mobile 2003, Win Mobile 5.0 and 6.0, Supports Palm OS 4.1 and up.

Opzioni/Modelli

Available NFC standard.

SDK with SDiD 1020(P.N. 9916-050-10).

Note

Sample software included.

SDK not included (ask for developer Kit).

Prezzo unitario indicativo per quantitativi d'ordine di inferiori a 9 pezzi.

Contattateci per quantitativi superiori.

Link Datasheet