

RFID HF Wall Mount Ethernet (PoE) proximity controller - MultiISO



Frequenza/Standard 13,56 MHz. ISO 15693, ISO 14443-A/-B & NFC devices (ISO 18092) Interfacce...

Valutazione: Nessuna valutazione

[Fai una domanda su questo prodotto](#)

Manufacturer [FEIG](#)

Description

Frequenza/Standard

13,56 MHz.

ISO 15693, ISO 14443-A/-B & NFC devices (ISO 18092)

Interfacce & I/O

Ethernet 10BaseT - 100BaseTX automatic MDI/MDI-X cross over correction. TCP/IP protocol.

2 LED – Beeper

Antenna

Integrated

Applicazioni

Wall Mount Controller.

Fidelity Card, Access Control, ePayment, eTicketing, Public Transport etc.

Dati Tecnici

Power supply: Power over Ethernet (PoE) or 12-24 V AC/DC with external power supply unit (not include)

Power cons.: max. 3 Watt

RF Power: 250 mW +/- 2 dB.

Dati Fisici

Dimension: 84.2x84.2x22 mm. (surface mount).

Housing: Plastic ASA, Front: acrylic glass.

Protection class IP 54

Opzioni/Modelli

I/O Board ID CPR.I/O-A:

2 x Digital Inputs (max. cable length 3 m). 1 x Relay.

Note

Protocols FEIG ISO Host & Notification Mode.

AES 128 bit encryption.

Firmware Update (Flash)

MTBF: 338.000 h.

Surface spacer included.

Prezzo unitario indicativo per quantitativi d'ordine di inferiori a 9 pezzi.

Consultare per quantitativi superiori.

[Link Download](#)