RedWave Mid Gate UHF-EPC LAN Ethernet I/O high performance





ID RED.MGU200-E.

Valutazione: Nessuna valutazione
Fai una domanda su questo prodotto

ManufacturerSoftWork

Description

ID RED.MGU200-E. RedWave Mid Gate UHF-EPC LAN Ethernet I/O high performance. Gate Solution (pair of antennas), standard EPC Class 1 Gen 2 - ISO 18000-6C. Host Interfaces: Lan Ethernet RJ45 (10/100) & RS232. Operating frequency: 860 to 960 MHz (software adjust). RF power up to 300 mW. Read Range up to 300 cm (depending on tag & physical environment). UHF Antennas: 2 internal multiplexed (Gain: 9,0 dBic). Digital Input/Output optocoupler & Relè (24 V DC/ 2A). Optical Led Strip. Dimension: 1700 x 500 mm. metal base included. DRM (Dense Reader Mode). Reader modes: FEIG ISO Host, Scan mode, Buffering Read mode & Notification mode. Firmware upgradable. Protection class: IP20. Included 24 VDC Power Supply. CD with SW driver, SDK/Library (MS Window) & Sample Software.

Prezzo unitario indicativo per quantitativi d'ordine di inferiori a 9 pezzi.

Contattateci per quantitativi superiori.

Link Datasheet