RedWave Slim Gate UHF WiFi I/O





ID RED.SGU80-W.

Valutazione: Nessuna valutazione
Fai una domanda su questo prodotto

ManufacturerSoftWork

Description

ID RED.SGU80-W. RedWave Slim Gate UHF WiFi I/O. Gate Solution (pair of antennas), standard EPC Class 1 Gen 2 - ISO 18000-6C. Host Interfaces: Wireless Ethernet IEEE 802.11b. Operating frequency: 860 to 960 MHz (software adjust). RF power up to 170 mW. Power consumption: max. 2 W. Read Range up to 150 cm (depending on tag & physical environment). UHF Antennas: 2 internal multiplexed (Gain: 4,0 dBic). Digital Input/Output optocoupler. 2 x Relay (24 V DC/ 2A). Optical Led Strip & internal buzzer. Dimension (HxWxD): 1530 x 263 x 54/127 (top/base) mm. (metal base not included). Reader modes: FEIG ISO Host Mode, Scan Mode. Firmware upgradable. Protection class: IP20. Included 12 V Power Supply. CD with SW driver, SDK/Library (MS Window) & Sample Software.

Prezzo unitario indicativo per quantitativi d'ordine di inferiori a 9 pezzi.

Contattateci per quantitativi superiori.

Link Datasheet